



- NOTES:
1. CONCRETE: 5,000PSI MIN AFTER 28 DAYS.
  2. ALL REINFORCEMENT PER ASTM C1227-93.
  3. TEES AND GAS BAFFLE SOLD SEPARATELY.
  4. TONGUE & GROOVE JOINT SEALED WITH BUTYLE RESIN.
  5. 4" POLYLOK IV CLOSED END BOOTS USED FOR CONNECTIONS.
  6. PLASTIC RISER CAN BE POURED INTO COVER.

|   |      |          |                                     |                     |              |
|---|------|----------|-------------------------------------|---------------------|--------------|
| PREPARED FOR:   |      |          | ANDREW J. FOSS CO. INC.             |                     |              |
|   |      |          | 100 COCHECO ROAD                    |                     |              |
|   |      |          | FARMINGTON, NH 03835                |                     |              |
|   |      |          | PHONE(603)755-2515 FAX(603)278-7878 |                     |              |
| REV.NO.   | DATE | REVISION | DATE: 9/16/09                       | SHEET TITLE: SKETCH | DRWN BY: GJP |
|   |      |          | SCALE: N.T.S.                       |                     | CKD BY: KMK  |
| PREPARED BY:  |      |          | PROJECT: 4000 GALLON TANK H-20      |                     |              |
| <p>184 COURT STREET, BINGHAMTON, NY 13901<br/>TEL: (607) 231-6800 FAX: (607) 231-6850</p> |      |          | CONTRACTOR:                         | DWG. I.D.           | SK-01        |
|   |      |          | DELTA PROJ. NO.:                    | 2009.367.001        | SHT. NO.     |